Revision Date: 06/01/2015 Issue date: 06/01/2015

1 Identification

- · Product identifier
 - · Trade name: Air Intake Cleaner

· Part number: 400-2018

- · Application of the substance / the mixture air intake cleaner
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

Motorvac, division of, CPS Products Canada Ltd.

1324 Blundell Road

Mississauga, ON, L4Y 1M5

Canada

Phone: (905) 615-8620

· Emergency telephone number:

CHEMTREC International +1 (703) 527-3887 (outside the US), 1-800-424-9300 (in the US) 24 hr

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child. Repr. 2

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways. Asp. Tox. 1

- · Label elements
 - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









· Signal word Danger

· Hazard-determining components of labeling:

toluene

acetone

· Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 2)

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

(Contd. of page 1)

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Pressurized container: Do not pierce or burn, even after use.

Wash thoroughly after handling.

Do not spray on an open flame or other ignition source.

Wear protective gloves / eye protection / face protection.

If swallowed: Immediately call a poison center/doctor.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Additional information: For Professional Use Only
- · Classification system:
 - · NFPA ratings (scale 0 4)



Health = 2 Fire = 4 Reactivity = 3

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 4 Reactivity = 3

- · Other hazards
 - · Results of PBT and vPvB assessment
 - PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · **Description:** Mixture: consisting of the following hazardous components.

· Chemic	· Chemical components:		
67-64-1	acetone	25-50%	
108-88-3		20-<25%	
1330-20-7	xylene	20-<25%	
123-42-2	4-hydroxy-4-methylpentan-2-one	1-≤2.5%	
	propane	1-≤2.5%	
	isobutane	1-≤2.5%	
124-38-9	carbon dioxide	1-≤2.5%	

- US

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
 - · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Wash with soap and water for 20 minutes or until chemical is removed. Immediately remove all contaminated clothing. If skin irritation occurs, get medical attention. Launder contaminated clothing before reuse and discard leather articles saturated with the material.

· After eye contact:

Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Frost bites

Coughing

Nausea

Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

Cause nose, throat, and lung irritation.

Skin irritant

• Indication of any immediate medical attention and special treatment needed Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
 - For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture See section 10 for additional information.
- · Advice for firefighters
 - · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA 29 CFR 1910.1200 HCS

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
 - · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 - · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

 Components with limit values that requir 	e monitoring at the workplace:
--	--------------------------------

67-64-1 acetone (25-50%)

PEL TWA: 2400 mg/m³, 1000 ppm REL TWA: 590 mg/m³, 250 ppm

TLV STEL: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm TWA: (1188) NIC-594 mg/m³, (500) NIC-250 ppm

108-88-3 toluene (20-<25%)

PEL TWA: 200 ppm

CEV: 300; 500* ppm *10-min peak per 8-hr shift

REL STEL: 560 mg/m³, 150 ppm TWA: 375 mg/m³, 100 ppm

TLV TWA: 75 mg/m³, 20 ppm

BEI

1330-20-7 xylene (20-<25%)

PEL TWA: 435 mg/m³, 100 ppm REL STEL: 655 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm

(Contd. on page 5)

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

	(Contd. of page 4
TLV	STEL: 651 mg/m³, 150 ppm
	TWA: 434 mg/m³, 100 ppm
	BEI
	-42-2 4-hydroxy-4-methylpentan-2-one (1-≤2.5%)
	TWA: 240 mg/m³, 50 ppm
	TWA: 240 mg/m³, 50 ppm
	TWA: 238 mg/m³, 50 ppm
	08-6 propane (1-≤2.5%)
	TWA: 1800 mg/m³, 1000 ppm
	TWA: 1800 mg/m³, 1000 ppm
	refer to Appendix F
	28-5 isobutane (1-≤2.5%)
TLV	STEL: 2370 mg/m ³ , 1000 ppm
124-	-38-9 carbon dioxide (1-≤2.5%)
PEL	TWA: 9000 mg/m³, 5000 ppm
REL	STEL: 54.000 mg/m³, 30.000 ppm
	TWA: 9000 mg/m³, 5000 ppm
TLV	STEL: 54.000 mg/m³, 30.000 ppm
	TWA: 9000 mg/m³, 5000 ppm
07.0	· Ingredients with biological limit values:
	64-1 acetone (25-50%)
BEI	50 mg/L Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)
108-	-88-3 toluene (20-<25%)
BEI	0.02 mg/L
	Medium: blood
	Time: prior to last shift of workweek Parameter: Toluene
	Talamotor. Toldono
	0.03 mg/L
	Medium: urine
	Time: end of shift Parameter: Toluene
	Farameter. Toluene
	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
100	Parameter: o-Cresol with hydrolysis (background)
	0-20-7 xylene (20-<25%)
BEI	1.5 g/g creatinine Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids
	· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- Personal protective equipment:
 General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

(Contd. of page 5)

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Chemical resistant protective gloves

· Eye protection:



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

Information on basic physical and che	emical properties
· General Information	
· Appearance:	
· Form:	Aerosol
· Color:	Clear
· Odor:	hydrocarbon
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
 Melting point/Melting range: 	Undetermined.
 Boiling point/Boiling range: 	55 °C (131 °F)
· Flash point:	-17 °C (1 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	465 °C (869 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	13.0 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)
· Density at 20 °C (68 °F):	0.802 g/cm³ (6.693 lbs/gal)
· Relative density	Not determined.
Vapour density	Not determined.
 Evaporation rate 	Not applicable.

(Contd. on page 7)

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

(Contd. of page 6)

· Solubility in / Miscibility with

• Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent content:

· Organic solvents: 87.5 % · VOC content: 45.0 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity
 - · Chemical stability
 - · Thermal decomposition / conditions to be avoided:

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, open flames, sparks.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
Air Intake	Cleaner	
Oral	LD50	10780 mg/kg (rat) (ATE)
Dermal	LD50	10000 mg/kg (rabbit) (ATE)
67-64-1 ad	cetone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
108-88-3 t	oluene	
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)
1330-20-7	xylene	
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6700 mg/l (rat)
123-42-2	1-hydroxy	-4-methylpentan-2-one
Oral	LD50	4000 mg/kg (rat)
Dermal	LD50	13630 mg/kg (rab)
Drin	narv irrita	nt offoot:

- Primary irritant effect:
 - · on the skin: Irritant to skin and mucous membranes.

(Contd. on page 8)

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

(Contd. of page 7)

- · on the eye: Irritating effect.
- · Inhalation:

Do not inhale , can cause respiratory system irritation. asphyxiation

- · Ingestion: Result in central nervous system depression
- · Sensitization: No sensitizing effects known.
- · Route of Exposure skin, eye, inhalation
- · Subacute to chronic toxicity:

May cause skin defatting and dermatitis. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

· Carcinogenic categories

٠ ١٨	ARC (International Agency for Research on Cancer)	
108-88-3	toluene	3
1330-20-7	xylene	3
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- · Toxicity
 - · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Additional ecological information:
 - · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
 - · **PBT:** Not applicable.
 - · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

(Contd. of page 8)

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

UN-Number	
· DOT, IMDG, IATA	UN1950
UN proper shipping name	
· DOT	Aerosols, flammable
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
Transport hazard class(es)	
· DOT	
FLAMMARLE GAS.	
· Class	2.1
· Label	2.1
· IMDG, IATA	
2	
· Class	2.1
· Label	2.1
· Packing group · DOT, IMDG, IATA	Not Regulated
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Warning: Gases
· Danger code (Kemler): · EMS Number:	- F-D,S-U
· Transport in bulk according to Annex	<u> </u>
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg
· IMDG	
 Limited quantities (LQ) 	1L
 Excepted quantities (EQ) 	Code: E0
,	Not permitted as Excepted Quantity

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

(Contd. of page 9)

· UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · Sara
 - · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene 1330-20-7 xylene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
 - · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

· Carcinogenic categories

· EPA (Environmental Protection Agency)			
67-64-1	acetone	I	
108-88-3	toluene	Ш	
1330-20-7	xylene	I	

• TLV (Threshold Limit Value established by ACGIH) 67-64-1 acetone A4 108-88-3 toluene A4 1330-20-7 xylene A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS02 GHS04 GHS07 GHS08

Signal word Danger

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

(Contd. of page 10)

Hazard-determining components of labeling:

toluene

acetone

· Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Pressurized container: Do not pierce or burn, even after use.

Wash thoroughly after handling.

Do not spray on an open flame or other ignition source.

Wear protective gloves / eye protection / face protection.

If swallowed: Immediately call a poison center/doctor.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact: Engineering Department
 - · Issue Date June 1, 2015

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

(Contd. on page 12)

(Contd. of page 11)

Safety Data Sheet acc. to OSHA 29 CFR 1910.1200 HCS

Issue date: 06/01/2015 Revision Date: 06/01/2015

Trade name: Air Intake Cleaner

Repr. 2: Reproductive toxicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Asp. Tox. 1: Aspiration hazard, Hazard Category 1