CDS[®]



AVAILABILITY:

Item	Description	Size	Case Qt
OPEBM6S	AC/R Moisture Remover includes 1/4 SAE & 5/16 SAE clear flexible adapters	1 oz/30ml	15/per

Reference MSDS at cpsproducts.com for other important safety and handling information. Do not store in direct sunlight.



OPTIMA^M



eBOOST[™] AC/R Moisture Remover

eBOOST™ AC/R Moisture Remover is a professional chemical tool and dehydrating additive that eliminates moisture and prevents water molecules from forming in AC/R systems. Safe for all systems and compatible with all AB, mineral, POE and PAG oils. Will not break down or leave behind any type of particulate matter, acids, gels or polymers.

ADDITIONAL BENEFITS

- Eliminates system moisture
- Compatible with lubricants and all refrigerant gases – including CFC, HFC and HCFC
- Does not contain methanol or solid particles
- Treats up to 6 tons
- Safe and effective for all systems
- Packaged in sealed trilingual (English, French and Spanish) clamshell with hang tab, color insert card and instructions

EASY-TO-USE INSTRUCTIONS

- Turn AC/R system on and set to lowest temperature.
- 2. Hold syringe end upright and unscrew (remove) blue cap.
- 3. Select a ¼" hose (black o –ring) or 5/16" hose (green o-ring).
- 4. Attach threaded end of hose to syringe.
- 5. Gently push plunger and fill clear hose with solution (to displace all air from hose).
- 6. Connect hose to system low pressure service port and inject 100% of solution.
- 7. Disconnect hose/syringe from system and discard.
- 8. Continue to run system for 30 minutes.