



EGR Adapter

Mercedes Benz/Jeep 3.0L

Part No. 069-3383



CAUTION:

Always wear gloves and safety glasses when performing this service

Steps to perform service:

1. Add Part# 400-3012 DieselTune™ Max Strength Fuel Injector Cleaner to vehicle's fuel tank.
2. Remove plastic engine cover.
3. Remove Turbo Boost Pressure sensor from intake. Do not disconnect wire connector. Install 069-3383 in its place.
4. Attach aerator assembly to 069-3383. Ensure air valve and fluid valve are closed.
5. Unscrew fill cap and fill with 32oz (950mL) of Part# 400-0280 EGR Cleaner. For first application or severe coking, 64 oz. may be required.
6. Reinstall the fill cap and hang tool from the hood latch. Connect shop air. Set air pressure on Part# 500-0170 EGR Tool to 40-50 psi.
7. Start vehicle engine. Open Air valve, adjust regulator to maintain initial pressure then open the fluid valve on the tool.
8. Continue service until EGR tool is empty.
9. Turn the fluid and air valve on tool to the closed position. Turn Vehicle off. Detach shop air line and depressurize the tool by rotating the regulator knob counter clockwise.
10. Remove adaptors and reassemble vehicle components in the reverse order of removal.
11. Add one bottle of Part# 400-3022 DieselTune™ Complete Fuel Supplement to vehicle's fuel tank.

ISO 9001
CERTIFIED
ZIM14-01020